





RIGID TOE-PUFF WITH EVA ADHESIVE

PRODUCT DESCRIPTION

TALYN is an extruded material for toe-puffs, with a "ping-pong" effect. This Talyn is a rigid version with a traditional adhesive based on EVA with one backer.

TECHNICAL DATA

Talyn	Thickness* (mm)	Cutting Direction
402 - TAG1	0,35 - 0,45	
403 - TAG1	0,45 - 0,55	
404 - TAG1	0,55 - 0,65	100
405 - TAG1	0,65 - 0,75	
406 - TAG1	0,80 - 0,90	
407 - TAG1	0,85 - 0,95	← 150
408 - TAG1	0,95 - 1,05	

^{*} All thickness values have a natural variation of ± 0,05mm

INSTRUCTIONS OF USE

The toe puff is applied by a special pneumatic pressing machine, equipped with heated curved plate, timer and thermostat.

Advisable working condition:

- Temperature: from 130°C to 150°C.
- Contact time: from 6 to 12 seconds according to the thickness of the article.
- - Minimum effective interface temperature: 100°C

We recommend you to carry out a preliminary test of bonding as the conditions of application may vary depending on the characteristics of the upper.

There is no binding time as to the lasting period.

ATTENTION: the application of solvent glue can affect the adhesive present on the sheet, causing detachment.

PRODUCT CHARACTERISTICS **RIGIDITY SOFT RIGID** SHAPE RETENTION





BENEFITS

- Excellent adaptability
- Ping-pong effect
- Highly moldable
- Recyclable Recycled

RECOMMENDED FOR









EM 01 11/11/2020







basis of our best actual knowledge